



FabMate™ NEUTRAL CURE LMN SILICONE

A neutral cure, low modulus premium performance silicone sealant designed for weather sealing and joint sealing in a wide range of applications in building and construction. Non-corrosive and odour free with outstanding adhesion to a wide range of materials.

- **Perimeter sealing**
- **Sealed unit fitting**
- **100% solvent free silicone**
- **Excellent weatherproof and UV resistance - No shrinkage or yellowing**
- **No Cracking or Shrinking**
- **Water resistant**
- **Very low odour and noncorrosive**
- **Excellent flexibility and adhesion to numerous porous and non-porous substrates for construction and glazing applications.**
- **Fast curing, low modulus, high elasticity.**
- **High viscosity non slump formula.**
- **Wide range of application temperatures – from +5C to +40C**
- **Excellent resistant to temperature extremes once cured - - 60C to +180C**
- **Mould resistant – ideal for high moisture and high humidity environments such as bathrooms and kitchens**



Unit 3 Earl Road, Rackheath, Norwich NR13 6NT

01603 722077 sales@fabmate.co.uk www.fabmate.co.uk

Application

Applications include perimeter sealing, connection and expansion joint sealing, embedding sealed units and sanitary area sealing. Excellent flexibility and adhesion to a wide range of materials.

Standards

EN 15651 – 1 (Facades)

EN 15651 – 2 (Glazing)

EN15651 – 3 (Sanitary areas)

Refer to **TDS** and **SDS** for further detailed information.

Colours

Available in **Clear** and **White** in **310ml** cartridge.

Product Code Clear: FM06LMCL

Product Code White: FM06LMWH



Unit 3 Earl Road, Rackheath, Norwich NR13 6NT

01603 722077 sales@fabmate.co.uk www.fabmate.co.uk